
2-Line, Uni-directional, Ultra-low Capacitance, Transient Voltage Suppressor




Features


- Stand-off voltage: 5V Max
- Transient protection for each line according to IEC61000-4-2(ESD): ±20kV (contact) IEC61000-4-5(surge): 3.5A (8/20μs)
- Ultra-low capacitance: C_J = 0.4pF typ.
- Low leakage current: I_R <1nA typ.
- Low clamping voltage: V_{CL} = 14.0V typ. @ I_{PP} = 16A (TLP)
- Solid-state silicon technology
- Halogen-free

Mechanical Data

- **Package**: SOT-23
- **Terminals**: Tin plated leads, solderabl per J-STD-002 and JESD22-B102
- **Marking:**



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	42	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	3.5	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±20	KV
ESD according to IEC61000-4-2 contact discharge		±20	
Junction temperature	T_J	125	°C
Operating temperature	T_{OP}	-40~85	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics（T_a=25 Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				5
Reverse leakage current	I_R	nA	V_{RWM} = 5V		<1	100
Reverse breakdown voltage	$V_{(BR)}$	V	I_T = 1mA	7	8	9
Forward voltage	V_F	V	I_T = 10mA	0.6	0.9	1.2
Clamping voltage 1)	V_{CL}	V	I_{PP} = 16A, t_p = 100ns		14	
Dynamic resistance 1)	R_{DYN}	Ω			0.33	
Clamping voltage 2)	V_{CL}	V	V_{ESD} = 8kV		14	
Clamping voltage 3)	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs			10
		V	I_{PP} = 3.5A, t_p = 8/20μs			12
Junction capacitance	CJ	pF	V_R = 0V, f = 1MHz Any I/O pin to GND		0.4	0.65
			V_R = 0V, f = 1MHz Between any I/O pin		0.25	0.4

Notes:


1) TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
2) Contact discharge mode, according to IEC61000-4-2.
3) Non-repetitive current pulse, according to IEC61000-4-5.


■Ordering Information (Example)


PREFERED P/N	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDSLC5V0E	3000	30000	120000	7 reel


■ **Characteristics** (Typical)


µ


























■ Outline Dimensions





■ Soldering Footprint



Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.