P-Channel Enhancement Mode Field Effect Transistor

Product Summary

- V_{DS} -20 V
- I_D -35 A
- $R_{DS(ON)}$(at V_{GS}=-4.5V) 13 mΩ
- $R_{DS(ON)}$(at V_{GS}=-2.5V) 18 mΩ
- $R_{DS(ON)}$(at V_{GS}=-1.8V) 29 mΩ
- 100% EAS Tested

General Description

- Trench Power LV MOSFET technology
- High density cell design for Low RDS(ON)
- High Speed switching
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- Battery protection
- Power management
- Load switch

■ **Absolute Maximum Ratings** (T_A=25 unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	-20	V
Gate-source Voltage		V_{GS}	±10	V
Drain Current	T_A=25	I_D	-8	A
	T_A=100		-5	
	T_C=25		-35	
	T_C =100		-22	
Pulsed Drain Current [A]		I_{DM}		A
Avalanche energy [B]		EAS	98	mJ

■ Electrical Characteristics (T_J=25 unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=-250μA	-20	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-20V, V_{GS}=0V	-	-	-1	μA
		V_{DS}=-20V, V_{GS}=0V, Tj=150	-	-	-100	
Gate-Body Leakage Current	I_{GSS}	V_{GS}= ±10V, V_{DS}=0V	-	-	±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=-250μA	-0.4	-0.62	-1	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS}=-4.5V, I_D=-20A	-	10	13	mΩ
		V_{GS}=-2.5V, I_D=-15A	-	13.5	18	
		V_{GS}=-1.8V, I_D=-10A	-	19	29	
Diode Forward Voltage	V_{SD}	I_S=-20A, V_{GS}=0V	-	-	-1.2	V
Gate resistance	R_G	f=1MHz	-	13	-	Ω
Maximum Body-Diode Continuous Current	I_S		-	-	-35	A
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{DS}=-10V, V_{GS}=0V, f=1MHz	-	2010	-	pF
Output Capacitance	C_{oss}		-	270	-	
Reverse Transfer Capacitance	C_{rss}		-	240	-	
Switching Parameters						
Total Gate Charge	Q_g	V_{GS}=-4.5V, V_{DS}=-10V, I_D=-17A	-	23.6	-	nC
Gate-Source Charge	Q_{gs}		-	3.2	-	
Gate-Drain Charge	Q_{gd}		-	5.9	-	
Reverse Recovery Charge	Q_{rr}	I_F=-17A, di/dt=100A/us	-	76	-	nC
Reverse Recovery Time	t_{rr}		-	81	-	ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=-4.5V, V_{DD}=-10V, ID=-17A R_{GEN}=6Ω	-	9	-	ns
Turn-on Rise Time	t_r		-	15	-	
Turn-off Delay Time	$t_{D(off)}$		-	147	-	
Turn-off fall Time	t_f		-	88	-	

A. Repetitive rating; pulse width limited by max. junction temperature.

B. T_J=25 , V_G=-5V, R_G=25Ω, L=1mH, IAS=-14A.

C. P_d is based on max. junction temperature, using junction-case and junction-ambient thermal resistance.

D. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in the still air environment with T_A =25 . The maximum allowed junction temperature of 150 . The value in any given application depends on the user's specific board design.

Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics

Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage





Figure 6. Normalized On-Resistance



0

Figure 7. $R_{DS(on)}$ VS Drain Current



Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area


■ DFN3333-8L-A-0.8MM Package information




Top View

Bottom View

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	3.15	3.25	3.35
E	3.15	3.25	3.35
A	0.70	0.80	0.90
A1		0.20 BSC	
A2			



Side View



Suggested Solder Pad Layout
Top View

Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.10mm.
3.The pad layout is for reference purposes only.

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http://www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.