
MMSTA92

RoHS
COMPLIANT

PNP Silicon High Voltage Transistor



Features

Mechanical Data

Package

Terminals

Marking:

Maximum Ratings

Item	Symbol	Unit	Conditions	Value

Electrical Characteristics

Item	Symbol	Unit	Conditions	Min	Max

MMSTA92

RoHS COMPLIANT

Other Characteristics


Item	Symbol	Unit	Conditions	Min	Max

Ordering Information


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE

■Characteristics


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-V_{CB}/V_{EB}




SOT-323 Package Outline Dimensions



DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	

SOT-323 Soldering Footprint



Disclaimer