
Ultra-Fast Recovery Diodes 30A FRED





Fea ' ' ' ' t FRED chip

- Low forward Voltage drop
- Fast reverse recovery time
- High frequency operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability

Typical Applications

●Typical applications are in switching power supplies,
. converters, freewheeling diodes, and reverse battery protection

Mechanical Data

- **Package**: TO-220AC
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: As marked

■Maximum Ratings (Tj=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	MUR3060L
Device marking code			MUR3060L
Repetitive Peak Reverse Voltage	V_{RRM}	V	600
Average Rectified Output Current @60Hz sine wave, R-load, T_C(FIG.1)	IO	A	30
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T_a=25	I_{FSM}	A	300
Current Squared Time @1ms≤t≤8.3ms Tj=25	I^2t	A^2s	373
Single Pulse Avalanche Energy @ Tp=40uS, Tj=25 ,L=15mH	EAS	mJ	210
Storage Temperature	T_{stg}		-55 ~ +175
Junction Temperature	T_j		-55 ~ +175
Junction capacitance @4V,1MHz	Cj	pF	160

■Electrical Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Instantaneous forward voltage drop per diode	V_{FM}	V	I_{FM}=30.0A @Tj=25		-	2.0	2.50
			I_{FM}=30.0A @Tj=125			1.65	2.0
DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	uA	V_{RM}=V_{RRM} Tj=25		-	-	5.0
	I_{RRM2}		V_{RM}=V_{RRM} Tj=125		-	-	200
Reverse Recovery Time	Trr	ns	I_F=0.5A I_{RM}=1A I_{RR}=0.25A Tj=25		-	28	50
			Tj=25	I_F=30A di/dt=-200A/us V_{RM}=400V	-	60.5	-
			Tj=125		-	96.98	-
Peak recovery current	I_{RRM}	A	Tj=25		-	3.53	-
			Tj=125		-	11.3	-
Reverse recovery charge	Qrr	nC	Tj=25		-	106.7	-
			Tj=125		-	537.25	-

■Thermal Characteristics Tj=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	MUR3060L
Thermal Resistance	Between junction and case	$R_{\theta J-C}$	/W	2.0
	Between junction and Air	$R_{\theta J-A}$	/W	50

■Ordering Information (Example)

PREFERED P/N	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR3060L	Approximate 1.8	50	1000	5000	Tube

■ Characteristics(Typical)




FIG3: Forward Voltage




FIG.4: Instantaneous Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



TO-220AC		
Dim	Min	Max
A	9.95	10.35
B	2.55	2.95
C	3.75	4.05
D	14.95	15.25
E	3.75	4.25
F	0.26	0.5
G	0.68	0.94
H	13.3	13.9
I	4.86	5.26
J	4.38	4.78
K	1.14	1.4
L	2.37	2.79

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.