

Surface Mount Ultrafast Rectifier Diode





Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Solder dip 260 °C max. 10 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

Mechanical Data

- **Package**: DO-214AB (SMC)
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: Color band denotes the cathode end

■Maximum Ratings (T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	MURS340
Device marking code			MURS340
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	400
Maximum RMS Voltage	V_{RMS}	V	280
Maximum DC blocking Voltage	V_{DC}	V	400
Average Rectified Output Current @60Hz sine wave, Resistance load, TL ! l Ч p _ C			
	FSM	A	100
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			200
Current squared time @1ms≤t≤8.3ms Tj=25	I^2t	A^2s	41.5
Storage Temperature	T_{stg}		-55 ~ +150
Junction Temperature	Tj		-55 ~ +150

■Electrical Characteristics T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MURS340
Maximum	ş	_	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj

■Dynamic Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25	I_F=1A di/dt=-50A/us V_{RM}=30V	-	40	-
			Tj=25	I_F=3A di/dt=-200A/us V_{RM}=200V	-	32	-
			Tj=125		-	52	-
Peak recovery current	I_{RRM}	A	Tj=25		-	4.8	-
			Tj=125		-	7.5	-
Reverse recovery charge	Qrr	nC	Tj=25		-	76.5	-
			Tj=125		-	196.6	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25	I_R=0.8 A L=15 mH	4.8	-	-

■Thermal Characteristics T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	MURS340
Typical Thermal resistance	$R_{\theta J\text{-}A}$(1)	/W	50
	$R_{\theta J\text{-}L}$(1)		20
	$R_{\theta J\text{-}C}$(1)		15

Note(1)
Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MURS340	F1	Approximate 0.248	3000	/	42000	13” reel

■ Characteristics(Typical)

FIG.1: Io-TL Curve





FIG.2: Forward Surge Current Capadility






FIG.4: Typical Reverse Characteristics







FIG.5: Diagram of circuit and Testing wave form of reverse recovery time






■ Outline Dimensions



DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20

■ **Suggested pad layout**



DO-214AB (SMC)	
Dim	Min
P1	9.9
P2	3.84
Q1	3.03
Q2	3.82

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.