

Low VF Bridge Rectifiers





Features

- UL recognition, file #E230084
- based on silicon planar process
- Low VF
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package**: JA
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25 Unless otherwise specified

PARAMETER		SYMBO	UNIT	D25JAU80
Device marking code				D25JAU80
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	V	800
Maximum RMS Voltage		V_{RMS}	V	560
Maximum DC blocking Voltage		V_{DC}	V	800
Average Rectified Output Current @60Hz sine wave, R-load	With heatsink T_C =105	I_O	A	25.0
	Without heatsink T_a =25			4.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25		I_{FSM}	A	360
Current squared time @1ms≤t≤8.3ms Tj=25 ,rating of per diode		I^2t	A^2S	538
Storage temperature		T_{stg}		-55 ~ +150
Junction temperature		T_j		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		V_{dis}	KV	2
Mounting torque @Recommend torque 5kg cm		Tor	kg cm	8

■Electrical Characteristics T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V_F	V	I_{FM}=12.5A	0.80	0.89	0.92
DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25	-	0.005	5
			T_j=125	-	-	50
Junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	80	155	310

■Thermal Characteristics T_a=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	D25JAU80
Thermal Resistance	Between junction and ambient, Without heatsink	$R_{\theta J-A}$	/W	18.0
	Between junction and lead, With heatsink	$R_{\theta J-L}$		2.5
	Between junction and case, With heatsink	$R_{\theta J-C}$		1.0

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
D25JAU80	B1	Approximate 4.3	15	750	1500	Tube

■ Characteristics(Typical)

FIG1:Io-Tc Curve






FIG2:Surge Forward Current Capability



■ Outline Dimensions



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.