

RoHS
COMPLIANT





- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

- : JA
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- : Tin plated leads, solderable per J-STD-002 and JESD22-B102
- As marked on body

■ (T_a=25 Unless otherwise specified

Device marking code			D8JA05	D8JA10	D8JA20	D8JA40	D8JA60	D8JA80	D8JA100
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Average Rectified Output Current @60Hz sine wave, R-load, With heatsink T_C =118	I_O	A	8.0						
Average Rectified Output Current @60Hz sine wave, R-load, Without heatsink T_a =25	I_O	A	3.2						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25	I_{FSM}	A	175						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25	I_{FSM}	A	350						
Current squared time @1ms≤t≤8.3ms Tj=25 ,rating of per diode	I^2t	A^2S	127						
Storage temperature	T_{stg}		-55 ~ +150						
Junction temperature	T_j		-55 ~ +150						
Dielectric strength @ Terminals to case, AC 1 minute	V_{dis}	KV	2						
Mounting torque @Recommend torque 5kg cm	Tor	kg cm	8						

■ T_a=25 Unless otherwise specified

Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=4.0A	1.0						
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25	5						
			T_j=125	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	53						

■ T_a=25 Unless otherwise specified


Thermal Resistance	Between junction and ambient, Without heatsink	$R_{\theta J-A}$	/W	22						
	Between junction and case, With heatsink	$R_{\theta J-C}$		2						


Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.


■ (Example)


D8JA05 ~ D8JA100	B1	Approximate 4.3	15	750	1500	Tube

■ (Typical)










■



Dim	Min	Max
A	15.6	16.2
B	28.7	29.3
C	14.2	14.8
D	1.5	1.7
E	14.6	15.2
F	7.3	7.7
G	0.9	1.1
H	4.3	4.9
I	3.3	3.9
J	3.1	3.4
K	8.7	9.3
L	2.5	2.9
M	0.4	0.6
N	9.8	10.2

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.