

RoHS
COMPLIANT





- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

- : 6KBJ
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- : Tin plated leads, solderable per J-STD-002 and JESD22-B102
- As marked on body


■ (Ta=25 Unless otherwise specified

Device marking code				GBJ3512	GBJ3513
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	V	1200	1300
Maximum RMS Voltage		V_{RMS}	V	840	910
Maximum DC blocking Voltage		V_{DC}	V	1200	1300
Average rectified output current @60Hz sine wave, R-load	With heatsink Tc =90	I_O	A	35.0	
	Without heatsink Ta =25			4.0	

Forward Surge Current (Non-repetitive)
@60Hz Half-

Junction temperature	T_j		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute	V_{dis}	KV	2.5
Mounting torque @Recommend torque 5kg·cm	Tor	kg·cm	8

■



Dimensions in millimeters

Dim	Min	Max
A	29.7	30.3
B	19.7	20.3
C	17.0	18.0
D	4.8	5.8
E	3.8	4.2
F	7.3	7.7
G	9.8	10.2
H	0.9	1.1
I	2.0	2.4
J	2.3	2.7
K	3.4	3.8
L	4.4	4.8
M	10.8	11.2
N	3.1	3.7
O	3.1	3.4
P	0.6	0.8

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.