

RoHS
COMPLIANT





- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

- : 6KBJ a ŝ خ ξTin plated leads, solderable per Molding compound meets J-STD-002 and JESD22-B102
- As marked on body

■ (Ta=25 Unless otherwise specified

Device marking code				GBJL3506
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	V	600
Maximum RMS Voltage		V_{RMS}	V	420
Maximum DC blocking Voltage		V_{DC}	V	600
Average rectified output current @60Hz sine wave, R-load	With heatsink Tc =85	I_O	A	35.0
	Without heatsink Ta =25			3.5
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25		I_{FSM}	A	420
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25				840
Current squared time @1ms≤t≤8.3ms Tj=25 , Rating of per diode		I^2t	A^2S	730
Storage temperature		T_{stg}		-55 ~ +150
Junction temperature		T_j		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		Vdis	KV	2.5
Mounting torque @Recommend torque 5kg cm		Tor	kg cm	8

■ T_a=25 Unless otherwise specified

Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=17.5A	0.95
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25	5
			T_j=125	200
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	280

■ T_a=25 Unless otherwise specified


Thermal Resistance	Between junction and ambient, Without heatsink	$R_{\theta J-A}$	/W	18.0
	Between junction and case, With heatsink	$R_{\theta J-C}$		1.0


Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.


■ (Example)


GBJL3506	B1	Approximate 6.5	15	750	1500	TUBE

■ (Typical)










■



Dim	Min	Max
A	29.7	30.3
B	19.7	20.3
C	17.0	18.0
D	4.8	5.8
E	3.8	4.2
F	7.3	7.7
G	9.8	10.2
H	0.9	1.1
I	2.0	2.4
J	2.3	2.7
K	3.4	3.8
L	4.4	4.8
M	10.8	11.2
N	3.1	3.7
O	3.1	3.4
P	0.6	0.8

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.