

RoHS
COMPLIANT





- UL recognition, file #E230084
- Glass passivated chip junction
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

- : GBP
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- : Tin plated leads, solderable per J-STD-002 and JESD22-B102
- As marked on body

■ (T_a=25 Unless otherwise specified

	I_O	A	4.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25	I_{FSM}	A	110						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			220						
Current squared time @1ms≤t≤8.3ms Tj=25 , Rating of per diode	I^2t	A^2s	50						
Dielectric strength @ terminals to case, AC 1 minute	Vdis	KV	2						
Storage temperature	T_{stg}		-55 ~ +150						
Junction temperature	T_j		-55 ~ +150						

■ T_a=25 Unless otherwise specified

Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=2.0A	1.0						
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j =25	5						
			T_j =125	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	35						


■ T_a=25 Unless otherwise specified


Thermal Resistance	Between junction and ambient	$R_{\theta J-A}$	/W	45						
	Between junction and Case	$R_{\theta J-C}$		5						

■ (Example)


GBP4005 THRU GBP410	B1	1.4	35	2100	4200	TUBE

■ (Typical)





■



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.