

Low VF Bridge Rectifiers





Features

- UL recognition, file #E313149
- Glass passivated chip junction
- Ideal for automated placement
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

General purpose use in AC/DC bridge full wave rectification for SMPS, lighting ballaster, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

Mechanical Data

- **Package**: YBS3
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	YBSML8006
Device marking code			YBSML8006
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	600
Maximum RMS Voltage	V_{RMS}	V	420
Maximum DC blocking Voltage	V_{DC}	V	600
	o	A	8.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25	I_{FSM}	A	250
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			500
Current squared time @1ms≤t≤8.3ms Tj=25 Rating of per diode	I^2t	A^2s	259.4
Storage temperature	T_{stg}		-55 ~ +150
Junction temperature	T_j		-55 ~ +150

■Electrical Characteristics T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V_F	V	I_{FM}=4.0A	0.7	0.87	0.92
DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25	-	0.068	5

■Thermal Characteristics T_a=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	YBSML8006
Typical Thermal Resistance	Between Junction and Ambient	$R_{\theta J-A}$	/W	55
	Between Junction and Lead	$R_{\theta J-L}$		10
	Between Junction and Case	$R_{\theta J-C}$		5


Note: Device mounted on P.C.B with 35mm*25mm*1.7mm.

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YBSML8006	F1	Approximate 0.38	1800	/	25200	13'' Reel

■ Characteristics (Typical)

FIG3: Typical Forward Voltage




■ Outline Dimensions



YBS3		
Dim	**Min**	**Max**
A	10.00	10.40
B	9.70	10.10
C	6.80	7.20
D	1.3	1.5
E	1.4	1.8
F	0.5	1.1
G	0	0.15
H	4.9	5.1
T	0.20	0.30

■ Suggested pad layout



YBS3	
Dim	**Min**
P1	9.25
P2	5.00
Q1	1.00
Q2	1.5

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.